

Declaration of Performance

ICYFOAM WALL

DoP N° 0012/1-2019

Declared thermal resistance for all application thicknesses

1	Product name:	ICYFOAM WALL
2	Intended use:	Thermal insulation for buildings
3	Manufacturer:	ICYNENE INC 6747 Campobello Road, Mississauga, Ontario, Canada, L5N 2L7 +1 905 363 4040 www.icynene.com
4	Authorised Representative:	ICYNENE Europe S.P.R.L. Clos Chapelle des Champs, Boite 3030, 1200 Brussels, Belgium +32 (0)2 880 62 33 www.icynene.eu
5	System of AVCP:	System 3
6	Harmonized Standart:	EN 14315-1
	Notified Body:	NB 1020

Thickness (mm)	Declared aged thermal conductivity, λ_d (W/mK)	Thermal Resistance Rd (m ² K/W)
25	0,029	0,85
30	0,029	1,00
35	0,029	1,20
40	0,029	1,35
45	0,029	1,55
50	0,029	1,70
55	0,029	1,85
60	0,029	2,05
65	0,029	2,20
70	0,029	2,40
75	0,029	2,55
80	0,027	2,95
85	0,027	3,10
90	0,027	3,30
95	0,027	3,50
100	0,027	3,70
105	0,027	3,85
110	0,027	4,05
115	0,027	4,25
120	0,026	4,60
125	0,026	4,80
130	0,026	5,00
135	0,026	5,15
140	0,026	5,35
145	0,026	5,55
150	0,026	5,75
155	0,026	5,95
160	0,026	6,15
165	0,026	6,30
170	0,026	6,50
175	0,026	6,70
180	0,026	6,90
185	0,026	7,10
190	0,026	7,30
195	0,026	7,50
200	0,026	7,65
205	0,026	7,85
210	0,026	8,05
215	0,026	8,25
220	0,026	8,45
225	0,026	8,65
230	0,026	8,80
235	0,026	9,00
240	0,026	9,20
245	0,026	9,40
250	0,026	9,60

7. Declared performance

Characteristic	Performance	Harmonized Standard
Reaction to Fire	Euroclass E	EN 14315-1:2013
Water Permeability	W0,2	
Thermal Resistance	see attached table for values of declared thermal resistance	
Water Vapor Permeability	NPD	
Compressive Strength	CS(10\Y)200	
Durability of reaction to fire against ageing/ degradation	Reaction to fire does not decrease with time	
Durability of thermal resistance against ageing/ degradation (λ_d, R_d)	Declared thermal conductivity value after aging $\lambda_D = 0,026$ W/m.K, $\lambda_D = 0,027$ W/m.K or $\lambda_D = 0,029$ W/m.K depending the thickness, see attached table for values of declared thermal resistance	
Durability compressive strength against ageing/ degradation	NPD	
Continuous Glowing Combustion	NPD	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacture



Jan Vimr
Supply Chain Director
January 2019
DoP : Declaration of performance
CPR : Construction Product
Regulation Declaration of
Performance DoP 0012/1-2019